

## LavaPort-Quad

### PCI Bus Four Port 16650 Serial Board

#### Features & Benefits

- Adds four 16650 UART serial ports to PCI-equipped PCs
- Each port is capable of a maximum data throughput rate up to 460.8 kbps
- Each port includes integrated 64-byte FIFO buffer (16654 UART) with software configurable Rx/Tx triggers, 4x clock, and on-board flow control to guarantee errorless data transmission even at top speed
- All four ports share one PCI bus IRQ — even when accessed simultaneously, saving valuable resources for other expansion cards
- Compatible with RS-232 serial peripherals including 56K and ISDN modems, PDAs, digital cameras, bar-code scanners, and UPSes
- Includes “Lava Com Port Redirect” and “Lava Modem Speed Set” utility software for easy configuration of 230.4 kbps capable external modems
- Ideal for connecting four modems on a single card in SOHO and telecommuting server applications
- Easy Plug and Play installation — automatically selects next available IRQ and I/O addresses
- Compliant with PCI Specification 2.1
- Lava Lifetime Warranty

#### Connectors

- Four DB-9 male RS-232

#### System Requirements

- PCI host slot

Drivers ship with product. For updated software support visit [www.lavalink.com](http://www.lavalink.com).

FC CE

